

ST-1 STIHL Backpack Blower Rack Instructions

Thank you for purchasing a TrimmerTrap Product. The ST-1 protects all STIHL BR-300 and 400 series blowers. Select a mounting location which will not interfere with the pulling vehicle or equipment on the trailer. Make certain that any blower which will hang on the rack does not exceed the width of the widest part of the trailer. Check the mounting hardware daily. The blower tube must be removed or secured before transport. NOTE: TrimmerTrap's RC-3 Rubber Clamp works well for securing blower tubes. Attach the RC-3 rubber clamp to the trailer rail next to the ST-1.

The rack must be attached at two points along the upright at least 12 inches apart using a minimum of two 5/16" bolts and lock nuts. **Due to the many different construction techniques used on trailers, the hardware required to attach the rack is not included and must be acquired by the user.** When drilling the one inch square tube, be absolutely certain that the holes are centered in the tube. Install the blower by placing the bottom of the blower onto the two vertical uprights which are located about 2/3rds of the way down the tube. There are recesses in the bottom of the plastic frame which will slide on over the uprights. Next, pivot the top of the blower forward until the hole at the top of the blower frame aligns with the vertical stud (hang pin) extending from the rack. Slide the blower all the way onto the hang pin and install the retaining pin with de-dent ball into the vertical hole in the hang pin. Use the cable and sleeves supplied to make a lanyard for the retaining pin by attaching one end to the ring on the retaining pin and the other end to the rack. You can use pliers or a hammer to crimp the aluminum sleeves. A padlock can be installed into the horizontal hole at the end of the hang pin.

The ST-1 is not compatible with STIHL 500 and 600 series blowers. For STIHL 500 and 600 series blowers use a TrimmerTrap ST-2.

NOTE: IT IS THE PURCHASERS SOLE RESPONSIBILITY TO ASSURE THAT THE RACK IS INSTALLED SAFELY AND SECURELY TO A COMPONENT THAT WILL ADEQUATELY SUPPORT THE EQUIPMENT.

<u>ST-1 Parts List</u>	<u>Quantity</u>
cable	one
sleeves	two
end cap	one
retaining pin	one

WARRANTY: 90 days against defects in material and workmanship, TrimmerTrap, Inc. reserves the right to repair or replace at its sole discretion the alleged defective TrimmerTrap product. Determination of validity of alleged defect claim will be made upon goods returned to us freight prepaid to our location in Louisville, KY. Call 1-800-279-8727 for a return goods authorization.